

# Industrial Duct

Slogan: We deliver fresh air.

Name : PVC Elasticity Steel Wire Duct



## Construction:

PVC+high elasticity steel wire

## Product features:

- Great compressibility
- Lightweight duct
- Cost effective
- Easy installation
- Excellent flexibility

Application: Air, dust, fume, textile mills, woodworking shops, air duct cleaning, chemical fumes, material handling

Duct Construction : PVC elasticity steel wire duct

Wall Thickness : 0.02mm-0.025mm

Inner Diameter : 2"-24"(52mm-609mm)

Temperature Range : -30°C/+80°C

Air Velocity : 30m/s (max)

Operating Pressure : 2500pa

Standard Length : 10m

Fire Resistance : Non-fire resistant

Package : opp bag + carton or mixed passage

Slogan: We deliver fresh air.

Name : Canvas Duct



**Construction:**

PVC coated fabric galvanized steel

**Product features:**

- Wide temperature range
- Superior chemical resistance
- Durable
- Easy installation
- Excellent flexibility

Application: Air, dust, fume, air duct cleaning, HAVC system, electric equipment, workshop fumes, sewer

Duct Construction : PVC coated fabric galvanized steel

Wall Thickness : 0.4mm

Inner Diameter : 2"-48"(52mm-1220mm)

Temperature Range : -20°C/+300°C

Air Velocity : 45m/s (max)

Operating Pressure : 6000pa

Standard Length : 10m

Fire Resistance : Fire retardant

Package : opp bag + carton or mixed passage

Slogan: We deliver fresh air.

Name : PU Duct



**Construction:**

PU+coppered steel wire

**Product features:**

- Great abrasion resistance
- Lightweight duct
- Smooth inner surface
- Easy installation
- Excellent flexibility

Air, power, smoke, wood chip, textile mills,

Application: woodworking shops, air duct cleaning, chemical fumes, material handling

Duct Construction : PU+coppered steel wire

Wall Thickness : 0.3mm-1.5mm

Inner Diameter : 2"-24"(52mm-609mm)

Temperature Range : -30°C/+80°C

Air Velocity : 30m/s (max)

Operating Pressure : 2000pa

Standard Length : 10m

Fire Resistance : Non-fire resistant

Package : opp bag + carton or mixed passage